SICAM

WHAT'S BEHIND?

ITALIAN QUALITY



FALCO AL 520S

Falco AL 520 S is our best offer in terms of price and performance.
Equipped with a 20" turntable (external clamping), it's the right entry level tyre changer for low volume workshops.

Image shown above is indicative only.

ACCESSORIES



PN: 1695 101 402
Jaw plastic protection kit



PN: 1695 101 502
Jaw plastic protection kit



PN: 1695 101 608
Protective wing kit for mounting/ demounting head



PN: 1695 102 725
Protective wing for mounting/ demounting head



PN: 1695 106 152
Plastic guard for bead breaker tyre/rim protection



PN: 1695 105 191
Plastic protection for rim




PN: 1695 103 211
Plastic mounting/demounting head kit (with adapter)




PN: 1695 101 518
Bead breaking spacer for motor-bike wheels



PN: 1695 103 210
Motorbike mounting/demounting head kit




PN: 1695 103 542
Scooter adapter kit



PN: 1695 103 543
Kit adattatori moto/scooter



PN: 1695 101 575
Motorbike/scooter adapter kit



PN: 1695 106 190
Roller board



PN: 1695 108 913
External tubeless inflating device



PN: 1695 108 871
Mounting/demounting lever (WDK model)

TECHNICAL DATA

RANGE OF APPLICATION	FALCO AL 520 S
Mains connections	3 Ph – 400 V 50 – 60 Hz 1 Ph – 230 V 50 Hz 1 Ph – 110 V 60 Hz
External clamping	10″ – 20″
Internal clamping	12″ – 23″
Rim width	3″ – 11″
Max. wheel diameter	1000 mm
Bead breaker range	65 – 300 mm
Air connection	8 – 10 bar
Rotation speed	7,5 rpm
Dimensions max. (H x D x W)	1860 x 1660 x 1200 mm 1860 x 1660 x 1800 mm (V1)
Net weight	223 kg

SCOPE OF DELIVERY:


- 1x Lubricant brush
- 1x Bead lever

VARIANTS:




FALCO AL 520 S (B):
Basic version without plastics and inflating system

FALCO AL 520 S (EU):
Basic version ready for inflating system connection



FALCO AL 520 S (F):
Full version with Inflating gun system with pipe connections



FALCO AL 520 S (IT):
Full version with IT kit and plastics

Sicam S.r.l. Società Unipersonale
Via G. Corradini | 42015 Correggio RE Italy
Tel. +39 0522 643-311 | Fax +39 0522 637-760
E-mail: sales@sicam.it | www.sicam.it

Product technical specifications and images in this catalogue are not binding and may be varied in any way without notice.